


BJ153

内槽压板



| |
|--------|
| 本体 |
| S45C |
| 淬火回火 |
| 四氧化三铁膜 |

| 型 号 | L | W | H | W ₁ | L ₂ | M | L ₁ | L ₃ | 夹紧力(kN) 突出量 max.~min. | 容许紧固扭矩 (N·m) | 质量 (g) |
|-------------|-----|----|-----|----------------|----------------|----------|----------------|----------------|--------------------------|-----------------|-----------|
| BJ153-08040 | 40 | 19 | 12 | 9 | 6 | M 8×1.25 | 10 | 32 | 5.3~7.3 | 17 | 50 |
| BJ153-08050 | 50 | | | | 14 | | | 42 | 4 ~ 7.6 | | 60 |
| BJ153-08063 | 63 | | | | 27 | | | 55 | 3.1~8.3 | | 70 |
| BJ153-10050 | 50 | 25 | 12 | 11 | 8 | M10×1.5 | 12 | 40 | 8.5~11.9 | 34 | 80 |
| BJ153-10063 | 63 | | | | 18 | | | 53 | 6.4~12.2 | | 100 |
| BJ153-10080 | 80 | | | | 32 | | | 70 | 7.4~17.7 | | 170 |
| BJ153-10100 | 100 | 16 | 16 | 11 | 40 | M10×1.5 | 15 | 90 | 8.8~18.8 | 45 | 220 |
| BJ153-10125 | 125 | | | | 50 | | | 115 | 9.8~19.6 | | 280 |
| BJ153-12063 | 63 | | | | 14 | | | 14 | 52 | | 13.7~21.6 |
| BJ153-12080 | 80 | 25 | 69 | 10.3~21 | 240 | | | | | | |
| BJ153-12100 | 100 | 32 | 89 | 10.9~25.8 | 350 | | | | | | |
| BJ153-12125 | 125 | 19 | 13 | 50 | M12×1.75 | 20 | 114 | 12.9~27.5 | 80 | 440 | |
| BJ153-12160 | 160 | | | | | | 60 | 149 | | 15.4~28.8 | 570 |
| BJ153-16080 | 80 | | | | | | 19 | 17 | | 17 | M16×2 |
| BJ153-16100 | 100 | 38 | 85 | 14.2~28.4 | 540 | | | | | | |
| BJ153-16125 | 125 | 25 | 110 | 14.7~31.1 | 670 | | | | | | |
| BJ153-16160 | 160 | 25 | 65 | 65 | M20×2.5 | 32 | 145 | 15.3~33.4 | 129 | 850 | |
| BJ153-20160 | 160 | | | | | | 50 | 144 | | 16.5~35.6 | 1140 |
| BJ153-20200 | 200 | | | | | | 21 | 184 | | 17.9~37.8 | 1440 |

使用示例及使用方法

