

型 号	H ₁	L	W	H max.	M	H ₃	L ₂	L ₁	L ₃	L ₄	H ₂	夹紧力(kN) 突出量 max.~min.	容许紧固扭矩 (N·m)	质量 (kg)
BJ156-12063B1	25~50	63		86	M12×1.75	18	14	14	52		16	13.7~21.6	71	0.39
BJ156-12063B2	50~70			107		0.43								
BJ156-12063B3	80~105			141		0.49								
BJ156-12080B1	25~50	80		86		18	25		69			10.3~21		0.43
BJ156-12080B2	50~70			107		0.47								
BJ156-12080B3	80~105			141		0.53								
BJ156-12100B1	20~45	100	32	84		18	40		89	6	19	10.9~25.8	80	0.57
BJ156-12100B2	45~70			109		0.63								
BJ156-12100B3	75~100			139		0.64								
BJ156-12125B1	20~45	125		84		18	50		114			12.9~27.5		0.68
BJ156-12125B2	45~70			109		0.74								
BJ156-12125B3	75~100			139		0.96								
BJ156-12160B1	15~40	160		85	18	60		149		25	17.4~32.5	90	1	
BJ156-12160B2	40~65			110	1.06									
BJ156-12160B3	70~95			140	1.18									
BJ156-16080B1	40~60	80		106	24	17	18	65		19	16.6~26	115	1.33	
BJ156-16080B2	65~90			136	1.47									
BJ156-16080B3	95~130			176	1.35									
BJ156-16100B1	35~60	100		109	24	30		85	6	22	12.7~25.3		1.5	
BJ156-16100B2	60~90			139	1.64									
BJ156-16100B3	95~125			174	1.52									
BJ156-16125B1	35~55	38		107	24	45	25	110		25	14.7~31.1	129	1.67	
BJ156-16125B2	60~90			142	1.81									
BJ156-16125B3	90~125			177	1.71									
BJ156-16160B1	35~55	160		107	24	65		145		25	15.3~33.4		1.86	
BJ156-16160B2	60~90			142	2									
BJ156-16160B3	90~125			177	2									

使用示例及使用方法

