

CL-FSS

衬垫



(A型用)



(B型用)



(C型用)

本体
SUM24L
四氧化三铁膜

型 号	螺纹尺寸 (左旋螺纹)	外径 尺寸	高度	质量 (g)	适用螺栓	
					万向螺栓(参照P. 501)	滚花头螺栓(参照P. 498)
CL-1A-FSS	#8-36	4.8	5.1	0.5	BJ736-06***A	BJ737-06***A
CL-1B-FSS		9.5	7.6	2	BJ736-06***B	BJ737-06***B
CL-1D-FSS		6.4	5.6	0.5	BJ736-06***C	BJ737-06***C
CL-2A-FSS	#12-28	6.4	6.5	1	BJ736-08***A	BJ737-08***A
CL-2B-FSS		12.7	8.9	4	BJ736-08***B	BJ737-08***B
CL-2D-FSS		7.9	7.1	1	BJ736-08***C	BJ737-08***C
CL-3A-FSS	1/4-28	7.6	8	1.5	BJ736-10***A	BJ737-10***A
CL-3B-FSS		14.3	11.1	6.5	BJ736-10***B	BJ737-10***B
CL-3D-FSS		9.5	8.3	2	BJ736-10***C	BJ737-10***C
CL-4A-FSS	5/16-24	9.9	9.1	3	BJ736-12***A	BJ737-12***A
CL-4B-FSS		19.1	10.7	11.5	BJ736-12***B	BJ737-12***B
CL-4D-FSS		12.7	11.3	5.5	BJ736-12***C	BJ737-12***C
CL-5A-FSS	7/16-20	12.7	11.9	5.5	BJ736-16***A	BJ737-16***A
CL-5B-FSS		23.6	13.1	19.5	BJ736-16***B	BJ737-16***B
CL-5D-FSS		15.7	13.5	8	BJ736-16***C	BJ737-16***C

特 点

BJ736 | BJ737 的衬垫损坏时，替换用的零件。

注意 事项

衬垫的螺纹式样为左旋螺纹。