



RCS

圆形衬垫螺丝



本体	衬垫
S45CF 四氧化三铁膜	SKS93 四氧化三铁膜 HRC54 ~ 58

型号	M	L	d	L ₁	L ₂	W	R	最大承载能力 (静载荷) (kN)	质量 (g)
RCS 5×09	M 5×0.8	9	3	0.5	1.8	2.5	2.5	4.5	0.7
RCS 5×13		13							1.2
RCS 5×17		17							1.6
RCS 5×21		21							2.1
RCS 6×14	M 6×1	14.3	4	0.8	2.7	3	3	9	1.7
RCS 6×18		18.3							2.4
RCS 6×22		22.3							3.1
RCS 6×27		27.3							4.1
RCS 8×15	M 8×1.25	14.8	5.5	0.8	3.2	4	5	15	3.3
RCS 8×19		18.8							4.5
RCS 8×23		22.8							5.7
RCS 8×28		27.8							7.2
RCS 8×35		34.8							9.4
RCS10×19	M10×1.5	18.9	7	1.1	3.5	5	6	20	6.7
RCS10×23		22.9							8.9
RCS10×28		27.9							11.1
RCS10×35		34.9							14.5
RCS10×43		42.9							18.5

特点

通过球面形状的衬垫，以点的方式将工件固定住。

使用示例及使用方法

