

CAC7

CASTORS (C7 Series)



Original ELESa Model RE.C7



CAC7-PBL
(Fixed Bracket)







CAC7-SBF
(Swivel Bracket with Brake)



CAC7-CBF
(Swivel Bracket with Stud & Brake)

CAC7-FBL
(Swivel Bracket with Through Hole)





Wheel Covering	Wheel	Bearing	Bracket
Vulcanized rubber(anti-trace)	Polyamide	Steel (Tube)	Steel
Gray	Black	Zinc plated	Zinc plated



CAC7-PBL
(Fixed Bracket)

CAC7-SBL
(Swivel Bracket)

CAC7-SBF
(Swivel Bracket with Brake)



CAC7-CBL
(Swivel Bracket with Stud)

CAC7-CBF
(Swivel Bracket with Stud & Brake)

CAC7-FBL
(Swivel Bracket with Through Hole)

CAC7-FBF
(Swivel Bracket with Through Hole & Brake)

CAC7-PBL (Fixed Bracket)

Part Number	D	T	H	S ₁	P ₁	S ₂	P ₂	W	L	Load Capacity (N)	Weight (g)
CAC7-050PBL	50	20	67	38.5	38.5	44	44	55	55	350	200
CAC7-060PBL	60	24	83	39.5	39.5	48	48	60	67	500	260
CAC7-080PBL	80		104							550	340

CAC7-SBL (Swivel Bracket)

Part Number	D	T	H	S ₁	P ₁	S ₂	P ₂	W	L	A	Load Capacity (N)	Weight (g)
CAC7-050SBL	50	20	67	38.5	38.5	44	44	55	55	24	350	200
CAC7-060SBL	60	24	83			48	48	60	60	21	500	280
CAC7-080SBL	80		104							30	550	430

CAC7-SBF (Swivel Bracket with Brake)

Part Number	D	T	H	S ₁	P ₁	S ₂	P ₂	W	L	A	R*)	Load Capacity (N)	Weight (g)
CAC7-050SBF	50	20	67	38.5	38.5	44	44	55	55	24	80	350	240
CAC7-060SBF	60	24	83			48	48	60	60	21	84	500	400
CAC7-080SBF	80		104							30	91	550	500

*) Distance required to avoid interference.

CAC7-CBL (Swivel Bracket with Stud)

Part Number	D	T	H	M	Lf	D ₁	A	Load Capacity (N)	Weight (g)
CAC7-050CBL	50	20	66	M 8×1.25	15	35	24	350	180
CAC7-060CBL	60	24	83	M12×1.75	25	41	21	500	290
CAC7-080CBL	80		104				25	550	390

CAC7-CBF (Swivel Bracket with Stud & Brake)

Part Number	D	T	H	M	Lf	D ₁	A	R*)	Load Capacity (N)	Weight (g)
CAC7-050CBF	50	20	66	M 8×1.25	15	35	24	80	350	210
CAC7-060CBF	60	24	83	M12×1.75	25	41	21	84	500	360
CAC7-080CBF	80		104				25	91	550	460

*) Distance required to avoid interference.

CAC7-FBL (Swivel Bracket with Through Hole)

Part Number	D	T	H	d	D ₁	A	Load Capacity (N)	Weight (g)
CAC7-050FBL	50	20	66	For M10 screw	35	24	350	160
CAC7-060FBL	60	24	83	For M12 screw	41	21	500	250
CAC7-080FBL	80		104			25	550	340

CAC7-FBF (Swivel Bracket with Through Hole & Brake)

Part Number	D	T	H	d	D ₁	A	R*)	Load Capacity (N)	Weight (g)
CAC7-050FBF	50	20	66	For M10 screw	35	24	80	350	190
CAC7-060FBF	60	24	83	For M12 screw	41	21	84	500	320
CAC7-080FBF	80		104			25	91	550	430

*) Distance required to avoid interference.

Feature :

The brake simultaneously stops the swivel of the bracket's turning plate and the rotation of the wheel.

Reference

The instructions for choice and use of castors.