

CAE2

CASTORS (E2 Series)



Original ELESA Model RE.E2



CAE2-PBL
(Fixed Bracket)





CAE2-SBF
(Swivel Bracket with Brake)





CAE2-FBL
(Swivel Bracket with
Through Hole)



Wheel Covering	Wheel	Bearing	Bracket
Nitrile rubber(NBR) Shore A83 Black	Polypropylene Black	Steel (Tube) Zinc plated	Steel Zinc plated





CAE2-PBL
(Fixed Bracket)





CAE2-SBL
(Swivel Bracket)



CAE2-SBF
(Swivel Bracket with Brake)



CAE2-FBL
(Swivel Bracket with Through Hole)



CAE2-FBF
(Swivel Bracket with Through Hole & Brake)

CAE2-PBL (Fixed Bracket)

Part Number	D	T	H	w ₁	S ₁	P ₁	S ₂	P ₂	W	L	Load Capacity(N)	Weight (g)
CAE2-080PBL	80	25	107	9	75	45	80	60	100	85	650	360
CAE2-100PBL	100	30	128								800	480
CAE2-125PBL	125	37.5	156								1,100	710
CAE2-150PBL	150	40	182								1,300	930
CAE2-180PBL	180	45	219	11	105	73	105	85	140	114	1,800	2,110
CAE2-200PBL	200	50	240								2,250	2,500

CAE2-SBL (Swivel Bracket)

Part Number	D	T	H	w ₁	S ₁	P ₁	S ₂	P ₂	W	L	A	Load Capacity(N)	Weight (g)
CAE2-080SBL	80	25	107	9	75	45	80	60	100	85	39	650	640
CAE2-100SBL	100	30	128								35	800	730
CAE2-125SBL	125	37.5	156								37	1,100	1,060
CAE2-150SBL	150	40	182									1,300	1,310
CAE2-180SBL	180	45	219	11	105	73	105	87	140	110	56	1,800	2,400
CAE2-200SBL	200	50	240								2,250	2,720	

CAE2-SBF (Swivel Bracket with Brake)

Part Number	D	T	H	w ₁	S ₁	P ₁	S ₂	P ₂	W	L	A	R*	Load Capacity(N)	Weight (g)
CAE2-080SBF	80	25	107	9	75	45	80	60	100	85	39	120	650	820
CAE2-100SBF	100	30	128								35		800	880
CAE2-125SBF	125	37.5	156								37		1,100	1,200
CAE2-150SBF	150	40	182										1,300	1,450
CAE2-180SBF	180	45	219	11	105	73	105	87	140	110	56	156	1,800	2,690
CAE2-200SBF	200	50	240								2,250		3,000	

*) Distance required to avoid interference.

CAE2-FBL (Swivel Bracket with Through Hole)

Part Number	D	T	H	d	D ₁	A	Load Capacity(N)	Weight (g)
CAE2-080FBL	80	25	107	For M12 screw	73	39	650	550
CAE2-100FBL	100	30	128			35	800	680
CAE2-125FBL	125	37.5	156			37	1,100	960
CAE2-150FBL	150	40	182				1,300	1,250
CAE2-180FBL	180	45	214	For M20 screw	102	56	1,800	2,280
CAE2-200FBL	200	50	236			2,250	2,620	

CAE2-FBF (Swivel Bracket with Through Hole & Brake)

Part Number	D	T	H	d	D ₁	A	R*	Load Capacity(N)	Weight (g)
CAE2-080FBF	80	25	107	For M12 screw	73	39	120	650	680
CAE2-100FBF	100	30	128			35		800	750
CAE2-125FBF	125	37.5	156			37		1,100	1,100
CAE2-150FBF	150	40	182					1,300	1,390
CAE2-180FBF	180	45	214	For M20 screw	102	56	156	1,800	2,570
CAE2-200FBF	200	50	236			2,250		2,910	

*) Distance required to avoid interference.

Feature :

The brake simultaneously stops the swivel of the bracket's turning plate and the rotation of the wheel

Reference

The instructions for choice and use of castors.