

CAF5

CASTORS (F5 Series)



Original ELESA Model RE.F5



CAF5-PSL
(Fixed Bracket)









CAF5-SSF
(Swivel Bracket with Brake)



CAF5-FSL
(Swivel Bracket with Through Hole)


Wheel Covering	Wheel	Bearing	Bracket
Urethane (Thermosetting) Shore A95 Yellow	Die-cast aluminum	Steel (Tube) Zinc plated Steel (ball bearing)	Steel Zinc plated






CAF5-PSL **CAF5-PSL-H**
(Fixed Bracket)

CAF5-SSL **CAF5-SSL-H**
(Swivel Bracket)


CAF5-SSF **CAF5-125SSF-H**
(Swivel Bracket with Brake)




For M12 screw



CAF5-150SSF-H **CAF5-200SSF-H**
(Swivel Bracket with Brake)



CAF5-FSL
(Swivel Bracket with Through Hole)



CAF5-FSF
(Swivel Bracket with Through Hole & Brake)

Feature :

The brake simultaneously stops the swivel of the bracket's turning plate and the rotation of the wheel

Reference

The instructions for choice and use of castors.

CAF5-PSL (Fixed Bracket)

Part Number	D	T	H	w ₁	S ₁	P ₁	S ₂	P ₂	W	L	Load Capacity(N)	Weight (g)
CAF5-080PSL	80	25	107	9	75	45	80	60	100	85	2,000	520
CAF5-100PSL	100	30	128								2,000	690
CAF5-125PSL	125	35	156								2,200	890

CAF5-SSL (Swivel Bracket)

Part Number	D	T	H	w ₁	S ₁	P ₁	S ₂	P ₂	W	L	A	Load Capacity(N)	Weight (g)
CAF5-080SSL	80	25	107	9	75	45	80	60	100	85	39	2,000	720
CAF5-100SSL	100	30	128								35	2,000	940
CAF5-125SSL	125	35	156								37	2,200	1,140

CAF5-SSF (Swivel Bracket with Brake)

Part Number	D	T	H	w ₁	S ₁	P ₁	S ₂	P ₂	W	L	A	R*	Load Capacity(N)	Weight (g)
CAF5-080SSF	80	25	107	9	75	45	80	60	100	85	39	120	2,000	910
CAF5-100SSF	100	30	128								35		2,000	1,080
CAF5-125SSF	125	35	156								37		2,200	1,280

*) Distance required to avoid interference

CAF5-FSL (Swivel Bracket with Through Hole)

Part Number	D	T	H	A	Load Capacity(N)	Weight (g)
CAF5-080FSL	80	25	107	39	2,000	650
CAF5-100FSL	100	30	128	35	2,000	880
CAF5-125FSL	125	35	156	37	2,200	1,080

CAF5-FSF (Swivel Bracket with Through Hole & Brake)

Part Number	D	T	H	A	R*	Load Capacity(N)	Weight (g)
CAF5-080FSF	80	25	107	39	120	2,000	780
CAF5-100FSF	100	30	128	35		2,000	1,020
CAF5-125FSF	125	35	156	37		2,200	1,230

*) Distance required to avoid interference

CAF5-PSL-H (Heavy Duty / Fixed Bracket)

Part Number	D	T	H	w ₁	S ₁	P ₁	S ₂	P ₂	W	L	Load Capacity(N)	Weight (g)
CAF5-125PSL-H	125	35	161	9	75	45	80	60	100	85	3,500	970
CAF5-150PSL-H	150	40	200	11	105	73	105	85	140	114	6,000	2,190
CAF5-200PSL-H	200	50	250								7,500	2,480

CAF5-SSL-H (Heavy Duty / Swivel Bracket)

Part Number	D	T	H	w ₁	S ₁	P ₁	S ₂	P ₂	W	L	A	Load Capacity(N)	Weight (g)
CAF5-125SSL-H	125	35	161	9	75	45	80	60	100	85	48	3,500	1,390
CAF5-150SSL-H	150	40	200	11	105	73	105	87	140	110	70	6,000	3,180
CAF5-200SSL-H	200	50	250									7,500	3,940

CAF5-SSF-H (Heavy Duty / Swivel Bracket with Brake)

Part Number	D	T	H	w ₁	S ₁	P ₁	S ₂	P ₂	W	L	A	R*	Load Capacity(N)	Weight (g)
CAF5-125SSF-H	125	35	161	9	75	45	80	60	100	85	48	120	3,500	1,540
CAF5-150SSF-H	150	40	200	11	105	73	105	87	140	110	70	146	6,000	3,750
CAF5-200SSF-H	200	50	250										7,500	4,510

*) Distance required to avoid interference