

FG-N / FE

OIL LEVEL INDICATORS




ELESA Original Design HGFT. & HFTX.




FG-N
(Black Body)





FE
(Clear Body)



FG-N
(Black Body)



FE
(Clear Body)



Type	Body	Window	Indicator Panel	Packing Ring
FG-N	Polyamide plastic Glossy Finish Black	Special clear polyamide plastic (PA-T/AR)	Aluminum (A1050P)	Nitro rubber (NBR)
FE	Special clear polyamide plastic (PA-T)			

FG-N (Black Body)

Part Number	A	B	C	D	E	F	Screw Torque (N·m)	Weight (g)
FG-10N	3/8-PF	11	24	8	7	22	4 - 8	4
FG-13N	1/2-PF	14.5	28	10	8.5	24	6 - 8	6
FG-16N	3/4-PF	18	35	9.5		32	8-10	10
FG-21N	1 -PF	23	42.5	11	9.5	38	10-12	15
FG-25N	1 1/4-PF	30	50		9	46	12-15	30
FG-40N	2 -PF	40	68		11	62		60

FE (Clear Body)

Part Number	A	B	C	D	E	F	Screw Torque (N·m)	Weight (g)
FE- 9	1/4-PF	9	18	10	6	15	2 - 3	3
FE-12	3/8-PF	11	22	7.5	7	19	3 - 5	4
FE-15	1/2-PF	14	26	10.5	8	22	4 - 6	5
FE-20	3/4-PF	20	31.5		9	27	6 - 8	8
FE-24	1 -PF	25	40	11	10	34	8 - 10	12
FE-30	1 1/4-PF	30	47	11.5	13	40.5		20

- Screw-in mounting
- Working temperature :
Between -30°C and 100°C
- Do not mount these plugs on the water tank to avoid them from expanding due to water absorption.
- The **FE** type is unresistant to alcohol.