

SFK

PLASTIC LOBE KNOBS



Original ELESA Model VC.692



SFK

(Brass Threaded Insert)



SFK-CL

(White, S. Steel Threaded Insert)




SFK

(Steel Stud)




SFK-CR

(Brass Threaded Insert, Chrome Plated)



SFK **SFK-SUS** **SFK-CL** **SFK-CR**
(Threaded Insert)



SFK **SFK-SUS**
(Stud)

Type	Knob	Threaded Insert	Stud
SFK	Polyamide (Glass-fiber reinforced)	Brass	Steel (SUM22L) Zinc plated
SFK-SUS	Black matte	Stainless steel(SUS303)	Stainless steel(SUS303)
SFK-CL	Polyamide (Glass-fiber reinforced) White matte	Stainless steel(SUS303)	-
SFK-CR	Polyamide (Glass-fiber reinforced) Chrome Plated	Brass	-

SFK **SFK-SUS** (Threaded Insert,Black)

Brass Insert		Stainless Steel Insert		D	H	D ₁	S	M	Lf
Part Number	Weight (g)	Part Number	Weight (g)						
SFK25A	7	-	-	25	20	12	10	M 4×0.7	10
SFK25B	7	SFK25B-SUS	6					M 5×0.8	
SFK32A	15	-	-	32	22.5	14	12.5	M 5×0.8	10
SFK32B	14	SFK32B-SUS	15					M 6×1	
SFK40A	25	-	-	40	26	15	14	M 8×1.25	12
SFK40B	23	SFK40B-SUS	24					M 8×1.25	13
SFK50A	44	-	-	50	31	18	17	M 10×1.5	15
SFK50B	40	SFK50B-SUS	42					M 10×1.5	17
SFK60A	63	-	-	60	37	21	21	M 12×1.75	20
SFK60B	54	SFK60B-SUS	54					M 12×1.75	

SFK-CL (White, S. Steel Threaded Insert)

Part Number	D	H	D ₁	S	M	L _f	Weight (g)
SFK32B-CL	32	22.5	14	12.5	M 6×1	10	15
SFK40B-CL	40	26	15	14	M 8×1.25	13	24
SFK50B-CL	50	31	18	17	M10×1.5	17	42
SFK60B-CL	60	37	21	21	M12×1.75	20	54

SFK-CR (Threaded Insert, Chrome Plated)

Part Number	D	H	D ₁	S	M	L _f	Weight (g)
SFK32B-CR	32	22.5	14	12.5	M 6×1	10	14
SFK40B-CR	40	26	15	14	M 8×1.25	13	23
SFK50B-CR	50	31	18	17	M10×1.5	17	40
SFK60A-CR	60	37	21	21		20	63

SFK **SFK-SUS** (Stud, Black)

Steel Stud		Stainless Steel Stud		D	H	D ₁	S	M	L	
Part Number	Weight (g)	Part Number	Weight (g)							
SFK25A×6	6	-	-	25	20	12	10	M 4×0.7	6	
SFK25A×10	7	-	-						10	
SFK25B×10	8	SFK25B×10-SUS	8						M 5×0.8	16
SFK25B×16	9	SFK25B×16-SUS	9							20
SFK25B×20	10	-	-					M 6×1	10	
SFK25C×10	10	-	-						16	
SFK25C×16	11	-	-						20	
SFK25C×20	12	-	-						30	
SFK25C×30	14	-	-						16	
SFK32B×16	15	SFK32B×16-SUS	15					32	22.5	14
SFK32B×20	16	SFK32B×20-SUS	16	30						
SFK32B×30	19	SFK32B×30-SUS	19	30						
SFK40B×20	28	SFK40B×20-SUS	28	40	26	15	14	M 8×1.25	20	
SFK40B×30	32	SFK40B×30-SUS	32						30	
SFK40B×40	36	SFK40B×40-SUS	36						40	
SFK50B×20	47	SFK50B×20-SUS	47	50	31	18	17	M10×1.5	20	
SFK50B×30	57	SFK50B×30-SUS	57						30	
SFK50B×40	66	SFK50B×40-SUS	67						40	
SFK60B×30	69	SFK60B×30-SUS	70						60	37
SFK60B×40	80	SFK60B×40-SUS	81	40						
SFK60B×50	91	SFK60B×50-SUS	92	50						

Features:

- Knobs with a stainless-steel insert or stud are perfect for use on food processing machines, or equipment which emphasizes hygienic factors.
- Chrome-plated style is resistant to abrasion, friction, sea water, detergents, acetone, ethyl alcohol and chlorine solution.
- Suitable for use on machines or equipment where frequent cleaning is required.

Technical Information

Working temperature :
 -30 to 30 °C for **SFK**, **SFK-SUS**, **SFK-CL** types
 -30 to 80 °C for **SFK-CR** type

Caution

Use in hot or highly humid circumstances can deteriorate the plastic properties.