

TH-N

PLASTIC T-HANDLES




Original Elesa Model L.652




Tapped



Stud



Tapped



Stud

Handle	Insert	Stud
Glass-fiber reinforced polyamide plastic Black matte	Brass	Steel(S10C) Zinc plated

Tapped

Part Number	D	H	A	W	S	M	Lf	D ₁	Weight (g)
TH40N	41	28	13	13	18.5	M 6×1	16	9	16
TH55N	56.5	33	15	15	21.5		18	10	27
TH55NA						20	11		28
TH67N	68.5	37	16.5	16.5	24.5			M 8×1.25	25
TH80NA	82	41.5	20	20	25	M10×1.5	18		
TH80N								56	
TH95N	94	46	21	21	28.5	M12×1.75	18		66


Stud

Part Number	D	H	A	W	S	M	L	Weight (g)
TH40N ×20	41	28	13	13	18.5	M 6×1	20	17
TH55NA×20	56.5	33	15	15	21.5	M 8×1.25		28
TH67N ×25	68.5	37	16.5	16.5	24.5		25	38
TH80N ×30	82	41.5	20	20	25	M10×1.5	30	58
TH95N ×30	94	46	21	21	28.5	M12×1.75		68

Technical Information

Working temperature : Between -30°C and 130°C

Strength Data



Size	Tensile Stress (F)
40	2500N
55	3300N
TH-N 67	4500N
80	7000N
95	8000N

Notes:

Use in hot or highly humid circumstances can deteriorate the plastic material properties.