

VD3

RUBBER VIBRATION DAMPER (TAPPED / TAPPED)




Original Elesa Model DVA



VD3



VD3-SUS



Type	Body	Threaded Part
VD3	Natural Rubber Shore A55+/-5	SS400 Steel Zinc plated
VD3-SUS	Black	SUS304 stainless steel

Steel	Stainless Steel	D	H	M	Lf (*)	Max. load (N)	Max. deflection (mm)	Spring constant (N/mm)	Weight (g)
Part Number	Part Number								
VD3-0808M 3	VD3-0808M 3-SUS	8	8	M 3×0.5	3	85	2	43	1
VD3-1010M 4	VD3-1010M 4-SUS	10	10	M 4×0.7	4	100	2.5	40	2
VD3-1015M 4	VD3-1015M 4-SUS		15				3.75	27	3
VD3-1510M 4	VD3-1510M 4-SUS	15	10	M 4×0.7	4	325	2	163	4
VD3-1515M 4	VD3-1515M 4-SUS		15			280	3.75	75	6
VD3-1520M 4	VD3-1520M 4-SUS		20			234	5	47	8
VD3-2015M 6	VD3-2015M 6-SUS	20	15	M 6×1	6	227	1.5	151	13
VD3-2020M 6	VD3-2020M 6-SUS		20			430	5	86	16
VD3-2025M 6	VD3-2025M 6-SUS		25			433	6.25	69	19
VD3-2520M 6	VD3-2520M 6-SUS	25	20	M 6×1	6	620	5	124	26
VD3-2525M 6	VD3-2525M 6-SUS		25			529	6.25	85	29
VD3-2530M 6	VD3-2530M 6-SUS		30			524	7.5	70	25
VD3-3020M 8	VD3-3020M 8-SUS	30	20	M 8×1.25	8	1067	0.7	1524	39
VD3-3030M 8	VD3-3030M 8-SUS		30			1055	7.5	141	45
VD3-3040M 8	VD3-3040M 8-SUS		40			2100	10	210	53
VD3-4030M 8	VD3-4030M 8-SUS	40	30	M 8×1.25	8	1574	7.5	210	80
VD3-4040M 8	VD3-4040M 8-SUS		40			1397	10	140	98
VD3-5030M10	VD3-5030M10-SUS	50	30	M10×1.5	10	3300	7.5	440	125
VD3-5040M10	VD3-5040M10-SUS		40			2130	10	213	150
VD3-5050M10	VD3-5050M10-SUS		50			2188	11.25	194	125

*) Pay attention to the thread depth and confirm that there is no rattling or gaps after installation.

Reference

For product detail and notes for your choice, see "Instructions for choice and use of rubber vibration damper".