


VD4

RUBBER VIBRATION DAMPER (STUD)



Original Elesa Model DVA



Body	Threaded Part
Natural Rubber Shore A55+/-5 Black	SS400 Steel Zinc plated

Part Number	D	H	M	L	Max. load (N)	Max. deflection (mm)	Spring constant (N/mm)	Weight (g)
VD4-0808M 3	8	8	M 3×0.5	6	55	2	28	3
VD4-1010M 4	10	10	M 4×0.7	10	88	2.5	35	2
VD4-1015M 4		15			92	3.75	25	3
VD4-1510M 4	15	10	M 4×0.7	10	168	2	84	4
VD4-1515M 4		15			259	3.75	69	5
VD4-1520M 4		20			223	5	45	7
VD4-1530M 4		30			258	7.5	34	9
VD4-2010M 6	20	10	M 6×1	18	645	2.5	258	15
VD4-2015M 6		15			468	3.75	125	10
VD4-2020M 6		20			367	5	73	13
VD4-2030M 6		30			420	7.5	56	23
VD4-2515M 6	25	15	M 6×1	18	797	3.75	213	18
VD4-2517M 6		17			833	4.25	196	20
VD4-2520M 6		20			581	5	116	20
VD4-2530M 6		30			591	7.5	79	25
VD4-3015M 8	30	15	M 8×1.25	20	1023	3.75	273	30
VD4-3017M 8		17			1275	4.25	300	31
VD4-3020M 8		20			1014	5	203	35
VD4-3025M 8		25			1026	6.25	164	38
VD4-3030M 8	40	30	M 8×1.25	23	776	7.5	103	43
VD4-4020M 8		20			2500	5	500	55
VD4-4025M 8		25			1660	6.25	266	60
VD4-4030M 8		30			1480	7.5	197	73
VD4-4040M 8	50	40	M10×1.5	28	1403	10	140	83
VD4-5020M10		20			3460	5	692	90
VD4-5030M10		30			2520	7.5	336	118
VD4-5040M10		40			2760	10	276	140

Reference

For product detail and notes for your choice, see
"Instructions for choice and use of rubber vibration damper".